

# PROTECTIVE HEADWEAR

## V9 VENTED HARD HAT WITH RATCHET HARNESS

PRODUCT DATA SHEET: HHV9R-(COLOUR)



PRODUCT CODE:  
HHV9R-G



HHV9R-B



HHV9R-Y



HHV9R-O



HHV9R-W



HHV9R-FY



HHV9R-R



### FEATURES AND BENEFITS

#### HELMET

- Certified to AS/NZS 1801:1997 Occupational Protective Helmets.
- Complete with 9 ventilation points.
- Lightweight ABS plastic vented hard hat.
- Extended peak & rain gutter to assist with sun shade & help protect wearer from rain.
- Replaceable cotton sweatband.
- 25mm moulded earmuff slots to accommodate ProChoice hearing protection.

#### HARNESS

- Fits all head sizes: 53cm - 66cm.
- 6 point 25mm webbing ratchet harness.
- Quick & easy single hand adjustment ratchet whilst wearing the helmet.
- Padded swivel feature for advanced positioning on back of the head.
- Replacement harness code: HHR-V9

### AVAILABLE IN

PRODUCT CODE	UOM	MOQ	CTN QTY
HHV9R-(COLOUR)	EACH	1	20

Green (HHV9R-G), Blue (HHV9R-B), White (HHV9R-W), Fluoro Yellow (HHV9R-FY), Yellow (HHV9R-Y), Orange (HHV9R-O), Red (HHV9R-R).

### APPLICATIONS

The Pro Choice Safety Gear range of range hearing protection is ideal for protection against noise generated from a wide range of applications in both workplace and recreational environments.

Typical applications include but are not limited to:

Agriculture, Aviation, Automotive, Chemical manufacturing, Construction, Heavy engineering, Metal processing, Mining and Quarrying, Welding, Woodworking.

### PRODUCT DETAILS

<b>Helmet Material:</b>	ABS Plastic
<b>Harness Materials:</b>	HDPE/Polyester
<b>Weight:</b>	362g ± 2
<b>Colours:</b>	Green, Blue, White, Fluoro Yellow, Yellow, Orange, Red
<b>Size:</b>	53cm - 66cm



ADJUSTABLE



BREATHABLE



LIGHTWEIGHT



LOGO PRINTING



MODULAR



OSFA

### CARE INSTRUCTIONS

Upon issue, wearers name & date of issue should be printed on the label provided.

ProChoice hard hats should be inspected for any deterioration or damage prior to use. ProChoice hard hats with excessive damage (cracks, colour distortion or deep abrasions) should be disposed of.

Entire hard hat, including harness, should be cleaned with warm soapy water (avoid any solvents) on a regular basis & sweatband replaced.

Industry recommends hard hat shell be replaced after 3 years of working life.

Components of the hard hat harness may deteriorate during its normal working life, & as a result the harness should be replaced at intervals no longer than 2 years.

To extend your hard hat working life, avoid excessive exposure to UV & any solvents.

### HARD HAT PRINTING SERVICE

The need to distinguish workers in various occupations on a work site can be for safety or convenience.

For example, having a safety officer readily identified by the colour of their hard hat can improve efficiencies; while being aware of who is a visitor or sub-contractor can improve security.

To further enhance these advantages, ProChoice now offers a pad printing & a vinyl printing service that can customise hard hats - before a customer takes delivery.

Speak to your ProChoice sales representative about adding value to your hard hat sales by utilising our pad printing or vinyl cut print service.

### STANDARDS

#### CERTIFIED TO:

AS/NZS 1801:1997 Occupational Protective Helmets

To be used in conjunction with:

AS/NZS 1800:1998 Occupational Protective Helmets - Selection, Care & Use



AS/NZS1801:1997  
Lic SMK20500

#### PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,  
GNANGARA, WA 6077  
TECH SUPPORT: 1300 275 820  
CUSTOMER SERVICE: 1300 770 723  
EMAIL: INFO@PARAMOUNTSAFETY.COM

#### PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, HIGHBROOK,  
EAST TAMAKI, AUCKLAND 2013  
TECH SUPPORT: 0800 888 778  
CUSTOMER SERVICE: 0800 888 778  
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

PROCHOICESAFETYGEAR.COM  
PARAMOUNTSAFETY.COM

PRO  
PRO CHOICE SAFETY GEAR  
FROM  
PARAMOUNT  
SAFETY PRODUCTS